

**MATT COATED PAPER 90gsm - SUPERTACK –
KRAFT 85gsm**

Issue: 06/04/2012
Modification: 1
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	195 gsm ± 5%	ISO 536
Total caliper	190 µm ± 7%	ISO 534

FACE

White matt woodfree machine coated paper with good opacity

Substance	90 gsm ± 4	ISO 536
Caliper	88µm ± 6	ISO 534

ADHESIVE

Water emulsion acrylic based Supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, including paper, board, glass, steel

Peel adhesion	16.5/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14.4 N/inch ± 4	FINAT9
Min. application temp.	+5°C /+40°C	
Service temp. Range	-20°C/+90°C	

BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

SAFETY REGULATIONS

The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements
The adhesive coating meets the FDA 21 CFR 175.105 for contact with foodstuffs

APPLICATIONS

High quality multipurpose labels with matt finish: address, instruction, inventory labels etc.

Trials are recommended, by the purchaser, prior to use, to determine the suitability of the product to the intended substrate.

PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.
Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

Forest Stewardship Council certified material
Splits on the release paper, standard spacing 38mm or customized

SHELF LIFE AND USE

Three (3) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions