

GLOSS MC 80gsm – REMOVABLE – KRAFT 85gsm

Issue: 19/09/2011
Modification: 3
page 1/1

GENERAL PRODUCT CHARACTERISTICS

| | | |
|---------------|--------------|---------|
| Total weight | 183 gsm ± 6% | ISO 536 |
| Total caliper | 164 µm ± 7% | ISO 534 |

FACE

White gloss coated woodfree paper

| | | |
|-----------|------------|---------|
| Substance | 80 gsm ± 3 | ISO 536 |
| Caliper | 64 µm ± 4 | ISO 534 |

ADHESIVE

Water emulsion removable adhesive type. Good short and long-term removability from most substrates including treated cardboard, glass, steel and polyolefins

| | | |
|------------------------|------------------|--------|
| Peel adhesion | 0,6 N/inch ± 0,2 | FINAT1 |
| Shear test | 6h ± 2 | FINAT8 |
| Quick stick | 0,7 N/inch ± 0,2 | FINAT9 |
| Min. application temp. | -5°C / +50°C | |
| Service temp. Range | -20°C/+60°C | |

BACKING

One-side coated white kraft, solventless silicon coated

| | | |
|-----------|------------|---------|
| Substance | 85 gsm ± 3 | ISO 536 |
| Caliper | 87 µm ± 5 | ISO 534 |

SAFETY REGULATIONS

The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

APPLICATIONS

High quality multicolor labels for the cosmetic and pharmaceutical industry, promotion campaign and children activity books.

NB. the removing properties are influenced by the kind of application surface.

Trials are recommended, by the purchaser, prior to use, to determine the suitability of the product to the intended substrate.

Not suitable for application on paper surfaces, particularly coated and varnished papers.

PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

Forest Stewardship Council (FSC) certified material

Splits on the release paper, standard spacing 38mm or customized

SHELF LIFE AND USE

Two (2) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions