

**OFFSET UNCOATED PAPER 120 gsm
SEMI-PERMANENT - KRAFT 85 gsm**

Issue: 03/11/2014
Modification:1
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	222 gsm \pm 5%	ISO 536
Total caliper	240 μ m \pm 6%	ISO 534

FACE

White woodfree uncoated paper, high whiteness and opacity

Substance	120 gsm \pm 5	ISO 536
Caliper	138 μ m \pm 6	ISO 534

ADHESIVE

Water emulsion acrylic based semi-permanent type, high cohesion, weak initial adhesion and good final tack, for application on a wide variety of surfaces. Especially designed for conversion to small sizes

Peel adhesion	3.9/inch \pm 1	FINAT1
Shear test	35 h \pm 10	FINAT8
Quick stick	2.9 N/inch \pm 1	FINAT9
Min. application temp.	+5°C	
Service temp. Range	-10°C/+120°C	

BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm \pm 3	ISO 536
Caliper	87 μ m \pm 5	ISO 534

SAFETY REGULATIONS

The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

APPLICATIONS

Information and product labeling, mailings, promotional stickers when a high thickness is requested

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

PRINTABILITY

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- Splits on the release paper, standard spacing 38mm or customized.
- Material certified Forest Stewardship Council (FSC)

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions